

TOPKLEAN™ EL 606



**Polyvalent cleaning fluid for electronic assembly
with or without rinsing**

FEATURES

TOPKLEAN™ EL-606 has been developed for cleaning stencils and missprinted circuit boards, **without need of water rinsing**.

This product can be used :

- In a spraying machine,
- Or in a dipping machine, using ultra-sound or immersed jets.

SPECIFICATIONS

Density at 20°C	0.9 to 1 g/ml
pH pure product	neutral

CHARACTERISTICS

Appearance	colorless
Flash point	none
Water solubility	partial
Alcohol solubility	total

TOPKLEAN™ EL-606 does not contain any surface-active products.
Rinsing with water is not necessary.

PACKAGING

Plastic can 20 liters

STORAGE & SHELF LIFE

Store the product in closed packaging.
Shelf life 18 months

PROCESS PARAMETERS

- TOPKLEAN™ EL-606 can be used pure or diluted.
- The low working temperature and the inherent characteristics of TOPKLEAN EL-606 provide a wide range of applications and good compatibility with glues used to manufacture printing stencils.
- Rinsing with water is not necessary.

HSE

Refer to the safety data sheet before use.

No issues when used as recommended.

Although the conformity to ROHS 2002/95CE applies EQUIPMENT put on the market and not a component in particular, we warranty that this product contains less than 0.1% of mercury, lead, chromium VI, polybrominated biphenyls (PBB) and polybrominated diphenyl ethers (PBDE) and less than 0.01% for the cadmium, in accordance with the decision of The European Commission dated 18/08/2005, fixing the maximal concentration values.

This data is based on information that the manufacturer believe to be reliable and offered in good faith. In no event will INVENTEC be responsible for special, incidental and consequential damages. The user is responsible to the Administrative Authorities (regulations for the protection of the Environment) for the conformity of his installation.

FPW.SB.10065 004 – 18/10/2010