

Class II B2 Biological Safety Cabinet




LCD Display
Large digital display is easy to monitor all the safety parameters at a glance and ergonomically sized control panel improves user interface.




Work Zone
Work zone, made of 304 stainless steel, is surrounded by negative pressure.



Remote Control
All functions can be realized with it, making the operation much easier and more convenient.



UV Lamp
Emission of 253.7 nanometers for most efficient decontamination.



Front Window
Two-layer laminated toughened glass > 5mm, anti UV



Footmaster Caster
Universal caster with brake and leveling feet



Foot Switch
Adjust front window height by foot during experiment, to avoid airflow turbulence caused by arm movement.



Waterproof Socket
2 waterproof sockets are located in the side wall, for optimum convenience of using small devices inside the cabinet.

ADVANTAGE

1. Time reserve function.
2. Motorized front window.
3. HEPA filter life and UV life indicator.
4. Automatic air speed adjustable with filter block.
5. With memory function in case of power-failure.
6. Work area surrounded by negative pressure, it can ensure maximum safety in work area.
7. Most accessories are standard, which saves your money. There is no need to pay more.
8. Audio and visual alarm (filter replacement, window over height, abnormal air flow velocity, etc).
9. Remote control. All functions can be realized with it, making the operation much easier and more convenient.
10. Interlock function: UV lamp and front window; UV lamp and blower, fluorescent lamp; blower and front window
11. Foot switch. Adjust front window height by foot during experiment, to avoid airflow turbulence caused by arm movement.

TECHNICAL PARAMETERS

Model	BSC-1100IIB2-X	BSC-1300IIB2-X	BSC-1500IIB2-X	BSC-1800IIB2-X	
Internal Size (W*D*H)	940*600*660mm	1150*600*660mm	1350*600*660mm	1700*600*660mm	
External Size (W*D*H)	1100*750*2250mm	1300*750*2250mm	1500*760*2250mm	1873*775*2270mm	
Tested Opening	Safety Height 200mm(8")				
Max Opening	420 mm (17")	420 mm (17")	500mm (20")	480mm (20")	
Inflow Velocity	0.53±0.025m/s				
Downflow Velocity	0.33±0.025m/s				
Pre-Filter	Washable				
HEPA Filter	Two, 99.999% efficiency at 0.3µm, filter life indicator.				
Front Window	Motorized, two-layer laminated toughened glass ≥ 5mm, anti UV				
Noise	NSF 49 ≤ 61dB / EN 12469 ≤ 58dB				
UV Lamp	30W*1	30W*1	40W*1	40W*1	
	UV timer, UV life indicator, emission of 253.7 nanometers for most efficient decontamination.				
Illuminating Lamp	LED lamp				
	12W*2	14W*2	16W*2	16W*2	
Illumination	≥1000Lux				
Consumption	700W	850W	900W	1200W	
Waterproof Sockets	Two, total load of two sockets: 500W				
Display	LCD display: exhaust filter and downflow filter pressure, filter and UV lamp working time, inflow and downflow velocity, filter life, humidity and temperature, system working time etc.				
Control System	Microprocessor				
Airflow System	0% air re-circulation, 100% air exhaust				
Alarm	Abnormal airflow velocity; Filter replacement; Front window at unsafe height				
Exhaust Duct	4 meters PVC duct, Diameter:300mm				
Material	Work Zone: 304 stainless steel Main Body: Cold-rolled steel with anti-bacteria powder coating				
Work Surface Height	750mm				
Caster	Footmaster caster				
Power Supply	AC 220V±10%, 50/60Hz; 110V±10%, 60Hz (110V/60Hz is not applicable to BSC-1800IIB2-X)				
Standard Accessory	Illuminating lamp, UV lamp*2, base stand, remote control, foot switch, exhaust blower, exhaust duct, drain valve, waterproof sockets*2, pipe strap*2				
Optional Accessory	Water and gas tap, Electric height adjustable base stand				
Gross Weight	246kg	276kg	302kg	408kg	
Package	Main Body Exhaust Blower (W*D*H)	1230*990*1810mm 970*810*630mm	1460*1050*1800mm 970*810*630mm	1650*990*1810mm 970*810*630mm	2000*950*1820mm 970*810*680mm